



www.longrayfog.com
www.foggingmachine.com

THE ADVANCED MANUFACTURER OF SPRAYING EQUIPMENTS

TSB-35/TSB-35(W)

TOP-RANK QUALITY, EASY OF MAINTENANCE!



TSB-35



TSB-35(W)

Thermal Foggers

Fields of Application

We designed this machine mainly used for prevention and control disease and insect pests in forest. It is capable of dispensing oil based or water based insecticides, fungicides, germicides, disinfectants, and other chemical products as easily, effectively and economically. The TSB-35 is mainly used for control and against of disease and insect pests of plants of which its height is very high, such as rubber tree, coconut, palm, and much more.

TSB-35(W) is mainly used for control and against of disease and insect pests of plants of which its height is lower, such as low brush wood, and much more.



Treating the forest plants

TEL: +86-755-29683026 29683036

FAX: +86-755-29683056

E-mail: trade@szlrkj.com

TSB-35/TSB-35(W)

Feature

The **TSB-35/TSB-35(W)** is built from only the highest quality materials with rigorous quality control at all stages of assembly. It adopt stainless steel as the basic material to producing its main frame, this feature will give reliable usage with the very minimum of maintenance. It adopts excellent pulse-jet engines to produce a high output of dense fog for the control of virus and flying insects such as mosquitoes, gnats, sand flies and black flies in forest.

- 1.The working performance is very reliable, producing a high output of dense fog, the penetration and clinging of fog is well.



- 2.The range of spraying is up to 20m in vertically.



3. High-work- efficiency, economical, it only used pesticide 5-8g/acre.
4. The cooling system is efficient, stainless steel protecting shield, ensure it is safe to operator.
5. Most light in weight, it is easy of operation.
6. Longer lifespan, it is easy of maintenance.



TSB-35

TSB-35(W)

Technical Specification

Weight, empty	11kg TSB-35 /10kg TSB-35(W)
Dimensions (L x W x H)	1420 x 330 x 280mm TSB-35 , 700 x 345 x 950mm TSB-35(W)
Weight, empty (shipping data)	15.6 kg TSB-35 /14.5 kg TSB-35(W)
Dimensions (L x W x H),(shipping data)	1375 x 375 x 352mm TSB-35 , 1110 x 355 x 520mm TSB-35(W)
Solution tank capacity	6 L
Fuel tank capacity	1.2 L
Fuel consumption	1.5 l/h
Performance of combustion chamber	11.6 KW/15.8HP
Maximum flow rate	42l/h
Flow rate with oil	8-42l/h
Energy	2 x 1.5 V batteries
Pressure in the solution tank	0.25 bar
Pressure in the oil tank	0.06 bar